



3M™ Peltor™ Optime™ 101 Over-the-Head Earmuffs

Part Number: 3M-H7A

3M™ Peltor™ Optime™ 101 Over-the-Head Earmuffs (H7A) for effective hearing conservation and protection.

<div itemprop=""> <div>
</div> </div>

Colour	-----	Green/Black
Dielectric	-----	No
Length Of Use	-----	Reusable
Noise Reduction Rating	-----	27 Decibel
Product Type	-----	Earmuffs
Protection Style	-----	Over the Head
Size	-----	One Size Fits Most

Product Description

Optime cap-mounted earmuffs feature a stainless steel headband for consistent force and effective hearing protection.Noise Reduction Rating (NRR)*: 27dB. CSA Class A. *The NRR may overestimate the hearing protection provided during typical use. 3M recommends reducing the NRR by 50% for estimating the amount of noise reduction provided.

Product Advantages

- Effective up to 101 dBA
- Stainless steel headband distributes weight for low-pressure fit
- Earcup pivot points that tilt for optimum comfort and efficiency
- Liquid/foam filled earmuff cushions
- Color-coding for compliance sighting

Technical Documents

3M Education

How to Use the Noise Reduction Rating (NRR)

The NRR describes the average sound level reduction (attenuation) provided by a hearing protection device (HPD) in a laboratory test. Since the NRR is based on laboratory testing, it does not take into account the loss of protection that occurs when hearing protectors are not fit properly or when they are not worn for the entire time that the wearer is exposed to noise.

For most wearers, the NRR identified on the current EPA label (shown here) significantly overestimates the protection of the hearing protector in the workplace. This rating is based on an "experimenter fit" method of measuring HPD attenuation.

Using the EPA Noise Reduction Rating (Experimenter Fit)

The NRR on the EPA label shown to the right is based on the average amount of attenuation provided by an HPD when it is worn by 10 different people during a laboratory test. During this test, the person conducting the test fits the hearing protector on each person. This "experimenter fit" method results in ratings as high as 33 dB. Since research indicates that these ratings overestimate the protection that many wearers will receive in the real world, **3M RECOMMENDS REDUCING THE NRR** before attempting to estimate the effectiveness of an HPD as follows:

1. Subtract 7 dB from the NRR if noise is measured on the A-weighted decibel scale (dBA). (Skip this step if noise is measured on the C-weighted dB scale)
2. Divide the result of step 1 (NRR-7) by 2. This is known as "derating".

in the real world. For more information about the NRR (SF), contact 3M Technical Service at 800 243-4630.

Estimating Noise Reduction for Individual Users

The labeled values of noise reduction are based on laboratory tests. It is not possible to use these data to reliably predict levels of protection achieved by a given individual in a particular environment. To ensure

An Example of Reducing the NRR

8-hour TWA noise exposure: 93 dBA
 NRR of hearing protectors: 29 dB
 Subtract 7 dB from the NRR: $29 \text{ dB} - 7 \text{ dB} = 22 \text{ dB}$
 Divide by 2: $22 \div 2 = 11 \text{ dB}$
 Subtract 11 dB from the 8-hour TWA noise exposure: $93 \text{ dBA} - 11 \text{ dB} = 82 \text{ dB}$
 Decide if 82 dB (known as the "Protected Exposure") is below the PEL for noise

A New Rating: NRR (SF)

A new "subject fit" method of measuring HPD attenuation will be used in the future to calculate a different rating: the NRR (SF). The people (subjects) in this laboratory test fit their own protector according to the manufacturer's instructions without the help of the person conducting the test. Compared to the NRR shown on the current EPA label, the NRR (SF) is usually a lower rating that may be closer to the performance of the hearing protector

protection, those wearing hearing protectors for occupational exposures must be enrolled in a hearing conservation program. Non-occupational users should have a hearing evaluation by an audiologist, physician, or other qualified professional, on a regular basis.




Hearing Protection

Noise Reduction Rating 25 DECIBELS
(When used as directed)

THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30 (HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS).

Minnesota Mining and Manufacturing Company - St. Paul, MN 55144-1000 **1260**

Federal law prohibits removal of this label prior to purchase.  LABEL REQUIRED BY U.S. E.P.A. REGULATION 40 CFR PART 211, Subpart B

United States
 Technical Service 1 800 243-4630
 Sales Assistance 1 800 896-4223
 2000 Resource Guide

G12

Canada
 Technical Service 1 800 267-4414
 Sales Assistance 1 800 265-1840 ext. 6137

View this product online at <https://marathonhardware.com/pd/3M-H7A>

