






Endura Inner Drawer 600mm Silk White

Part Number: 105-MSID238T-SW600

Included in this webkit		Qty Required
	Endura Softclose 600 white 238mm Part #: 105-MS238T-SW600	1
	Endura Inner Front Fixing 238 White Part #: 105-HD14014X-SW	1
	Drawer Front Internal 1100mm Silk White, Standard Part #: 105-HT10022-SW	1
	Cross Rail Square 1100mm Silk White Part #: 105-HT10071-SW	1

Legacy Endura Inner Drawer System Kit, 600mm Length, 238mm Height, Silk White, with Tilt Adjustment

Legacy Endura is a high-quality, cost-effective drawer system. With these internal drawer systems, you can offer a world of storage possibilities and truly impress your clients.

Adjustment Description	6-Way
Adjustments Included	with Tilt Adjustment
Closing Type	Soft-Close
Colour	Silk White
Drawer Side Height	238 mm
Drawer System	Legacy Endura
Drawer Type	Internal Drawer
Length	600mm (24in)
Load Capacity	40kg (88lbs)

Product Description



Legacy Endura is a high-quality, cost-effective drawer system. Available in two on-trend colours, Silk White and Matte Grey, Endura easily complements most colour schemes and projects. The allure of Legacy Endura is perfectly complemented by its reliability, meeting the needs of most homeowners and withstanding the strain and wear that regular use can have on its components. Upgrade from the standard doublewall drawer and truly impress your clients.

Product Advantages

- 8 choices of drawer length
 - 4 choices of drawer height: 88mm, 126mm, 172mm, and 238mm
 - 2 colour choices: Matte Grey & Silk White
 - Dynamic load capacity: 40kg (88lbs)
 - 2 choices of adjustments: 4-way adjustment (lateral and height) and 6-way adjustment (lateral, height, and tilt)
-




Technical Documents



LEGACY ENDURA

Technical Specifications & Assembly

Endura Internal Drawer Kit, 238mm F Height




Product Features

Transform your kitchen with the Legacy Endura internal drawer system, a high-quality and cost-effective solution available in elegant Silk White and stylish Matte Grey. Maximize your space by stacking multiple drawers within a custom pantry or base cabinet, making your kitchen both beautiful and efficient.

- Concealed full-extension soft-close slides
- 238mm drawer side height
- 6-way adjustment: Height (+/- 2mm), Lateral (+/- 1.5mm), Tilt (+0.5mm / -2.5mm)
- Tool free assembly and removal of drawer
- Dynamic load capacity: 40kg (88lbs)

Internal Drawer Kit (packaged as a complete set)

- One pair of Full Extension Soft-Close Slides
- One pair of Endura Drawer Sides
- One pair of inner cover caps
- One pair of support brackets for bottom panel
- Additional Parts Required:
 - One 13m cut-to-size aluminum drawer front
 - One 13m cut-to-size aluminum drawer rail
 - One pair of internal drawer front fixing brackets



Internal Drawer Kit Ordering Guide

Length (mm)	Length (Inch)	Matte Grey	Silk White
270mm	11"	105-MS238T-GM270	105-MS238T-SW270
300mm	12"	105-MS238T-GM300	105-MS238T-SW300
350mm	14"	105-MS238T-GM350	105-MS238T-SW350
400mm	16"	105-MS238T-GM400	105-MS238T-SW400
450mm	18"	105-MS238T-GM450	105-MS238T-SW450
500mm	20"	105-MS238T-GM500	105-MS238T-SW500
550mm	22"	105-MS238T-GM550	105-MS238T-SW550
600mm	24"	105-MS238T-GM600	105-MS238T-SW600

Additional Parts (Required)

Description	Part#
Legacy Drawer Front Internal 1100mm GM	105-HT10022-GM
Legacy Drawer Front Internal 1100mm SW	105-HT10022-SW
Legacy Cross Rail Square 1100mm GM	105-HT10071-GM
Legacy Cross Rail Square 1100mm SW	105-HT10071-SW
Front Fixing Plastic Bracket 238mm Height "Grey" for Inner Drawer	105-HD14014X-GM
Front Fixing Plastic Bracket 238mm Height "White" for Inner Drawer	105-HD14014X-SW

1

800.840.1228 / MARATHONHARDWARE.COM

View this product online at <https://marathonhardware.com/pd/105-MSID238T-SW600>

SGS

Page 1 of 4

The following sample(s) was / were submitted and identified on behalf of the client as:

Test Result Summary

Test(s) Requested	Result(s)
Slide durability test with reference to clause 6.3.8 of EN 15338:2007+A1:2010	PASS
Summary: 1. For further details, please refer to the following page(s).	



Intelsat otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed herein, available on request or accessible at <http://www.intelsat.com/Company%20Terms%20and%20Conditions>, or, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.intelsat.com/Terms-and-Conditions/Terms-E-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and arbitration clauses defined therein. Any holder of this document is deemed to have read, understood and agreed to the terms and conditions of the document and to be bound by the terms and conditions of the Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced or transmitted in any form or by any means electronic or mechanical, including photocopying, recording, or by any information storage or retrieval system, without prior written permission of the Company. The Company and its officers and employees may be prosecuted in the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

15. To verify the accuracy of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1683, or email: CN.Deechack@sage.com

Member of the SGS Group (SGS SA)

