



SynergySpacers for 1/4" Door Groove

Part Number: 25-1006

Synergy Panel Door Spacers for 1/4" Groove

SynergySpacers Panel Door Spacers - your economical, non-bleeding, and insertion tool friendly panel door spacer.

<div>
</div>

Colour	Tan
Diameter	0.265 in (6.7 mm)
Size	1/4 in

Product Description

SynergySpacers are the ideal product for constructing perfect panel cabinet doors. Marathon is your exclusive distributor in Canada.

There is absolutely no bleeding into your panel from the material used in these balls. The material is a unique composite that is not oil/petroleum based like others in the market. These spacers are insertion tool friendly for efficient and fast assembly. Finally your cost is more economical than the older standard spacer balls which have been well known to bleed and stain wooden doors.

Product Advantages

- No Oil, Carbon Black or Phthalates. Absolutely no bleeding into your panel door!
- No process or tool changes. Use the same insertion tools and efficient assembly process.
- Go GREEN and save some money too! Pricing beats the competition!

Important Information

If you are currently using a insertion machine with a petroleum/neoprene/oil-based round ball panel spacers, it is critical that you need to thoroughly clean your insertion machine (to remove any oil residue) before running Synergy Spacers through the insertion tool. Clean your tool with soap and warm water, but do not use thinners. This is a one-time cleaning that will get your machine ready for SynergySpacers and will not be necessary again. Talc is not necessary or advisable when inserting SynergySpacers.

Product Application



- Use 8-10 SynergySpacers per door.
- Compress so they are snug but not too tight.
- Frame Channel Suggestion: 0.235 to 0.25 inch (15/64" to 1/4")
- Panel Size Allowance Suggestion: 0.125 to 0.1875 inch. (1/8" to 3/16")



Technical Documents



View this product online at https://marathonhardware.com/pd/25-1006

Technical Documents

FASTENERS F HARDWARE



Now available in Canada exclusively by Marathon.

Part# 25-1006

The 100% GREEN Choice for Door Panel Spacing

- ☑ Eliminate panel rattle and cracking glue joints
- ☑ Allow for wood expansion and contraction
- ☑ Easily centre panels during assembly



Saving you Time

Saving you Money

Eliminate Frustration



- No Oil, Carbon Black or Phthalates.
- ☑ Absolutely no bleeding into your panel door!
- Use same insertion process as Spaceballs.
- ☑ Go GREEN and save money too!

Assembly Suggestions

SynergySpacers should fit snug but not too tight.

Frame Channel: 0.235 to 0.25 inch (15/64" to 1/4")

Panel Size Allowance: 0.125 to 0.1875 inch (1/8" to 3/16")

on Top, Bottom, Left and Right.

Number of SynergySpacers: 8 to 10 per door recommended.

** Other Sizes available upon request **

Other Sizes available upon request

RICHNO

Please login to our website to see your everday low pricing Bag Qty: 5000 pcs. Case Qty: 40,000 pcs.

Minimum Order: 5000 pcs.

CONTACT YOUR SALES REP TODAY FOR A FREE SAMPLE PACK!



Spaceball Users: You can use the same insertion machine, but it must be thoroughly cleaned with soap and warm water (not thinners) to remove any oil residue prior to running any SynergySpacers through the tool. With SynergySpacers, no talc is needed.

Mississauga	Barrie	Calgary	Edmonton	Kelowna	Surrey
905-607-8665	705-792-4416	403-291-2231	780-443-8092	250-765-8160	604-597-0175
Ontario	800-465-8665		Western Canada	800-840-1228	

www.marathonhardware.com

info@marathonhardware.com

View this product online at https://marathonhardware.com/pd/25-1006