



# Top Stays Lift System 960-2040PF Medium Weight

### Part Number: 105-SQ00AM

DTC Top Stays SQ Soft-Close Lift System 960-2040 PF Medium Weight

Hinge-less lift system from DTC is the perfect solution for upper cabinets. Heavy duty high quality steel mechanism, with infinity soft-close system.

Adjustment Type	3-Way
Angle	107
Application Type	Flap Door
Closing Type	- Soft-Close
Door Height Range	250 to 500 mm
Force	M (Medium)
Min. Cabinet Depth	240mm (9-1/2")
Opening Action	Progressive
Power Factor Range	960 - 2040

### **Product Description**

Attractive design and absolute functionality are the two most important aspects in today's kitchen. The Top Stays lift system offer just that through an inconspicuous look and a rugged, yet customizable design. The hinge-less lift system is an optimal upper cabinet solution for saving space and increasing access to multiple upper cabinets simultaneously.

Learn more about Top Stays

#### **Product Advantages**

- · 3 mechanism kits cover most common doors
- Stays open at any desired angle
- Opening angle and closing speed adjustments
- 3-way door gap position adjustments
- Integrated Infinity Soft-Close
- Certified for 60,000 cycles

How to Order? Calculate your Power Factor:

#### **Important Information**

- Cabinet Width: Supports up to 1200mm (47 1/4")
- Cabinet Height Range: 250 500mm (9 7/8 19 3/4")
- Door Thickness: 16–28mm (5/8 1 1/8")
- 107° door opening with optional restrictors


## **Product Application**

Perfect movement starts with correct power factor specific to your door's weight and height. If two factors align, we recommend to move up to the next strength or do a trial.

Top-Stays Power Factor Formula:

Power Factor = Overall Cabinet Height (mm) x Door Weight (kg, including 2x weight of handle)

\_\_\_\_\_





#### **Technical Documents**

	И	TOP S Technical Specificat	TAYS
Top Stay Standard Kit		Product Features	
		<ul> <li>No hinge required</li> <li>Opening angle: 107*</li> <li>Three lift mechanisms to cover all common widths and heights</li> <li>Silent and smooth closing</li> <li>Easy to open and stays at any desired angle</li> <li>Adjustable opening angle setting</li> <li>Three way adjustable door positioning</li> <li>Adjustable soft-close speed</li> <li>Tool free assembly and removal</li> <li>Third Party Certified for 60,000 cycles</li> </ul>	
fop Stays Kit (packaged as	a complete set)		
<ul> <li>One Top Stay Kit of Medium, Strong Dyn</li> <li>Includes two door m</li> </ul>	namic type		1 22
<ul> <li>Screw kit 4x11mm &amp;</li> </ul>		M4X11mm Ø4X16mm	
<ul> <li>Screw kit 4x11mm &amp;</li> <li>Fop Stays Kit Ordering Guide</li> </ul>	4xlómm	94X16mm	. I
Screw kit 4x11mm & Top Stays Kit Ordering Guide     Power Factor	4xlómm مع مراجع من علي و e Dynamic	Part# 04x16mm	Set/Box
Screw kit 4x11mm & fop Stays Kit Ordering Guide     Power Factor     580-1250	4x16mm میں 4 e Dynamic Light	Part# 105-SQ00AL	10
<ul> <li>Screw kit 4x11mm &amp;</li> <li>Fop Stays Kit Ordering Guide</li> <li>Power Factor</li> <li>580-1250</li> <li>960-2040</li> </ul>	4x16mm e Dynamic Light Medium	Part# 105-SQ00AL 105-SQ00AM	10 10
<ul> <li>Screw kit 4x11mm &amp;</li> <li>Stays Kit Ordering Guide</li> <li>Power Factor</li> <li>580-1250</li> </ul>	4x16mm میں 4 e Dynamic Light	Part# 105-SQ00AL	10
<ul> <li>Screw kit 4x11mm &amp;</li> <li>Fop Stays Kit Ordering Guide</li> <li>Power Factor</li> <li>580-1250</li> <li>960-2040</li> <li>1800-3500</li> </ul>	4x16mm e Dynamic Light Medium	Part# 105-SQ00AL 105-SQ00AM	10 10
<ul> <li>Screw kit 4x11mm &amp;</li> <li>Fop Stays Kit Ordering Guide</li> <li>Power Factor</li> <li>580-1250</li> <li>960-2040</li> <li>1800-3500</li> </ul>	4x16mm e Dynamic Light Medium	Part# 105-SQ00AL 105-SQ00AM	10 10
<ul> <li>Screw kit 4x11mm &amp;</li> <li>Stays Kit Ordering Guide</li> <li>Power Factor</li> <li>580-1250</li> <li>960-2040</li> <li>1800-3500</li> </ul>	4x16mm 4x16mm	Part# 105-SQ00AL 105-SQ00AM 105-SQ00AH	10 10 10
<ul> <li>Screw kit 4x11mm &amp;</li> <li>Top Stays Kit Ordering Guide</li> <li>Power Factor</li> <li>580-1250</li> <li>960-2040</li> </ul>	4x16mm 5trong 5trong Description	Part# 105-SQ00AL 105-SQ00AM 105-SQ00AH Part#	10 10 10 Set/Box
Screw kit 4x11mm & op Stays Kit Ordering Guide Power Factor 580-1250 960-2040 1800-3500 op Stays Cover Caps	4x16mm e Dynamic Light Medium Strong Description Cover Cap "Dark Grey" Cover Cap "White"	Part# 105-SQ00AL 105-SQ00AM 105-SQ00AH Part# 105-SQ1S-DG	10 10 10 Set/Box 20
Screw kit 4x11mm & fop Stays Kit Ordering Guide Power Factor 580-1250 960-2040 1800-3500 fop Stays Cover Caps	4x16mm e Dynamic Light Medium Strong Description Cover Cap "Dark Grey" Cover Cap "White"	Part# 105-SQ00AL 105-SQ00AM 105-SQ00AH Part# 105-SQ1S-DG	10 10 10 Set/Box 20
Screw kit 4x11mm & fop Stays Kit Ordering Guide Power Factor 580-1250 960-2040 1800-3500 fop Stays Cover Caps	4x16mm e Dynamic Light Medium Strong Description Cover Cap "Dark Grey" Cover Cap "White" ents	Part# 105-SQ00AL 105-SQ00AM 105-SQ00AH Part# 105-SQ3S-DG 105-SWJS-W	10 10 10 Set/Box 20 20
<ul> <li>Screw kit 4x11mm &amp;</li> <li>Fop Stays Kit Ordering Guide</li> <li>Power Factor</li> <li>580-1250</li> <li>960-2040</li> <li>1800-3500</li> </ul>	4x16mm 4x1mm 4x16mm 4x1	Part# 105-SQ00AL 105-SQ00AM 105-SQ00AH 105-SQ15-DG 105-SWJS-W Part#	10 10 10 20 20 Set/Box

View this product online at https://marathonhardware.com/pd/105-SQ00AM