



FastCap 2P10 Adhesive Thick 10oz

Part Number: F2P10THICK10OZ

FastCap 2P10 Adhesive Thick 10oz Bottle

Two-Part Ten-Second (2P10) Adhesive in 10oz Bottle with Flex-Tip Neck.

<div>
</div>

Type	Thick
Volume	10 oz

Product Description

This is part of the FastCap 2P-10 Adhesive program. As a two-part 10-second adhesive, just apply the adhesive and then spray the activator. This will enable anything to stick for a strong, permanent bond.

This Adhesive comes in a 10 oz. bottle with flexible neck for high volume use. Purchase activator separately.

Product Advantages

- Speed and strength
- 10 seconds to bond
- Start sanding within 60 seconds
- Dries crystal clear
- 4000 PSI tensile and sheer
- Breaks the wood, not the glue!

Product Application

Apply adhesive to your material and then spray the activator. Stick your materials together for a strong, permanent bond.



Technical Documents



5016 Pacific Highway
Ferndale, WA98248
Phone: 1-888-443-3748
Fax: 1-360-650-1075



Safety Data Sheet

Revision Date 10/11/19

Page 1/11

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY UNDERTAKING

1.1. Product Identifier

Product name	2P-10 SOLO THICK 2 O / 2P-10 THICK 10 OZ / 2P-10 RT THICK 2.25 / 2P-10 RT THICK 10 OZ / 2P-10 KIT / 2P-10 SOLOKIT
Product Grade	2P-10 THICK
CAS number	7085-85-0
EC number	230-391-5
REACH number	01-2119527766-29-0001

1.2. Relevant identified uses of the substance and uses advised against

Applications	Industrial adhesives application Consumer use of adhesives
--------------	---

1.3. Details of the supplier of the safety data sheet

Name	FastCap LLC
Address	5016 Pacific Highway Ferndale, WA 98248 USA
Telephone	1-360-752-2138
Fax	1-360-650-1075
Contact email	info@fastcap.com

1.4. Emergency telephone number

Chemtrec Telephone	1-800-262-8200
--------------------	----------------

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance

2.1.1. Classification of the product according to DSD (67/548/EC)

XI IRRITANT	R 36/37/38 Irritating to eyes, respiratory system and skin
-------------	--

2.1.2. Classification of the product according to CLP (1272/2008/EC)

Eye irrit. 2	H319 Causes serious eye irritation
STOT SE 3	H335 May cause respiratory irritation
Skin irrit. 2	H315 Causes skin irritation

2.2. Label elements according to CLP (1272/2008/EC)

Hazard pictograms



View this product online at <https://marathonhardware.com/pd/F2P10THICK10OZ>

